



BT-DHE

Hydraulic expansion chuck



Fig.1




Fig.2




Fig.3





Fig.4



• H : Depth of tool insertion (Min. ~ Max.)

- For more information on product features, see [27p](#)
- For more information on the related parts, see [33p](#)

	Model No.	ØD	L	ØD1	ØD2	L1	H	ADJ	Fig.	Kg	Package weight (Kg)
BT30	BT30-DHE6-65	6	65	29	46	33	30~39.8	M5	1	0.7	0.8
	BT30-DHE8-65	8	65	31	46	33	30~39.8	M5	1	0.7	0.8
	BT30-DHE10-65	10	65	32	46	34	35~44.8	M5	1	0.7	0.8
	BT30-DHE12-70	12	70	35	46	34	41~50.8	M5	1	0.8	0.8
	BT30-DHE14-90	14	90	36	46	40	43~52.8	M5	1	1.0	1.1
	BT30-DHE16-90	16	90	40	46	45	46~55.8	M5	1	1.0	1.1
	BT30-DHE18-90	18	90	42	46	40	49~58.8	M5	1	1.1	1.2
	BT30-DHE20-90	20	90	44	46	45	49~58.8	M5	1	1.1	1.2
BT40	BT40-DHE6-90	6	90	29	50	40	30~39.8	M5	1	1.4	1.6
	BT40-DHE6-140	6	140	29	50	40	30~39.8	M5	1	2.2	2.5
	BT40-DHE8-90	8	90	31	50	40	30~39.8	M5	1	1.4	1.6
	BT40-DHE8-140	8	140	31	50	40	30~39.8	M5	1	2.2	2.5
	BT40-DHE10-90	10	90	33	50	40	35~44.8	M5	1	1.5	1.7
	BT40-DHE10-140	10	140	33	50	40	35~44.8	M5	1	2.2	2.4
	BT40-DHE12-90	12	90	35	50	40	41~50.8	M10	1	1.5	1.7
	BT40-DHE12-140	12	140	35	50	40	41~50.8	M10	1	2.3	2.5
	BT40-DHE14-90	14	90	36	50	40	43~52.8	M10	1	1.5	1.7
	BT40-DHE14-140	14	140	36	50	40	43~52.8	M10	1	2.2	2.4
	BT40-DHE16-90	16	90	40	50	45	46~55.8	M10	1	1.5	1.7
	BT40-DHE16-140	16	140	40	50	45	46~55.8	M10	1	2.2	2.5
	BT40-DHE18-90	18	90	42	50	45	49~58.8	M10	1	1.5	1.7
	BT40-DHE18-140	18	140	42	50	45	49~58.8	M10	1	2.2	2.5
	BT40-DHE20-90	20	90	44	50	47	49~58.8	M10	1	1.5	1.7
	BT40-DHE20-140	20	140	44	50	50	49~58.8	M10	1	2.3	2.5
	BT40-DHE25-90	25	90	50	70	35	58~67.8	M16	2	2.0	2.2
	BT40-DHE25-105	25	105	57	-	78	51~61	M16	4	2.0	2.2
	BT40-DHE25-140	25	140	57	-	113	51~61	M16	4	2.6	2.9
	BT40-DHE32-90	32	90	63	75	35	58~67.8	M16	2	2.3	2.5
	BT40-DHE32-105	32	105	57	61	45	55~65	M16	3	2.4	2.6
	BT40-DHE32-140	32	140	57	61	45	55~65	M16	3	3.0	3.2

C Internal coolant system installed.