







Insert

Application	Picture	Designation	Coated							Uncoated		Dimensions (mm)						Configuration	Page
			NC3030	NC3120	NC3225	NC5330	NC6315	PC5300	PC8100	PC9030	H01	H05	b	r	l	d	t		
Parting off		MGMR 300-6D-PS										3.0	0.2	21	2.35	4.8	6		C30 C32
		8D-PS										3.0	0.2	21	2.35	4.8	5		
		15D-PS										3.0	0.2	21	2.35	4.8	15		
		400-4D-PS										4.0	0.3	21	3.30	4.8	4		
		500-4D-PS										5.0	0.3	26	4.10	5.8	4		
Parting off		MGML 300-6D-PS										3.0	0.2	21.0	2.35	4.8	6		
		8D-PS										3.0	0.2	21.0	2.35	4.8	5		
		15D-PS										3.0	0.2	21.0	2.35	4.8	15		
Parting off		MGMR 200-6D-PT										2.0	0.2	16	1.60	3.6	6		C30 C32
		300-6D-PT										3.0	0.2	21	2.35	4.8	6		
		8D-PT										3.0	0.2	21	2.35	4.8	8		
		15D-PT										3.0	0.2	21	2.35	4.8	15		
		400-4D-PT										4.0	0.3	21	3.30	4.8	4		
	500-4D-PT										5.0	0.3	26	4.10	5.8	4			
		MGML 200-6D-PT										2.0	0.2	16	1.60	3.6	6		
		300-6D-PT										3.0	0.2	21	2.35	4.8	6		
		8D-PT										3.0	0.2	21	2.35	4.8	8		
		15D-PT										3.0	0.2	21	2.35	4.8	15		
400-4D-PT											4.0	0.3	21	3.30	4.8	4			
500-4D-PT										5.0	0.3	26	4.10	5.8	4				
Aluminum		MRGN 300-A										3.0	1.5	21.0	2.35	4.8	-		C30 C31 C33 C34
		400-A										4.0	2.0	21.0	3.30	4.8	-		
		500-A										5.0	2.5	26.0	4.10	5.8	-		
		600-A										6.0	3.0	26.0	5.0	5.8	-		
		800-A										8.0	4.0	31.0	6.0	6.5	-		
Relief Profiling		MRMN 200-M										2.0	1.0	16.0	1.50	3.5	-		C30 ~34 C41
		300-M										3.0	1.5	21.0	2.35	4.8	-		
		400-M										4.0	2.0	21.0	3.3	4.8	-		
		500-M										5.0	2.5	26.0	4.1	5.8	-		
		600-M										6.0	3.0	26.0	5.0	5.8	-		
		800-M										8.0	4.0	31.0	6.0	6.5	-		

● : Stock item