

FMPC(M)3000





Fig. 2



AA
90°

- AR: 10°
- RR: -9° ~ -8°

(mm)

Designation			ØD	ØD ₂	Ød	a	b	E	F	Ød ₁	Ød ₂	ap		Fig.
FMPCM	3050HS	5	50	40	22	10.4	6.3	20	40	11	18	7	0.3	1
	3063HS	6	63	40	22	10.4	6.3	20	40	11	18	7	0.5	1
FMPC (FMPCM)	3080HS	7	80	55	25.4 (27)	9.5 (12.4)	6 (7)	25 (22)	50	14	20	7	1.0	1
	3100HS	8	100	67	31.75 (32)	12.7 (14.4)	8 (8)	36 (26)	50	18	45 (26)	7	1.5	2 (1)

() Metric size

Available inserts

SDET-MF

SDET-MM

SDET-MA

SDXT-MF

SDXT-MM

SDXT-MA



Designation		Cermet		Coated												Uncoated				page
		CN2000	CN30	NCM325	NCM335	NC5330	NCM535	NCM545	PC3600	PC3700	PC6510	PC9530	PC9540	PC5300	PC5400	PD2000	ST30A	G10	H01	
SDET	09M402R-MA															●				
	09M405R-MF																		●	●
	09M405R-MM																			
SDXT	09M405R-MF			●				●	●	●	●		●	●						
	09M405L-MF																			
	09M405R-MM			●	●				●		●		●	●						
	09M405L-MM							●		●										
	09M405R-MA																	●	●	


Available arbors

Designation	Ød	NC arbors
FMPCM 3050HS 3063HS	22	BT□□-FMC22-□□
FMPC 3080HS	25.4	BT□□-FMA25.4-□□
(FMPCM)	27	BT□□-FMC27-□□
	31.75	BT□□-FMA31.75-□□
3100HS	32	BT□□-FMC32-□□

Parts

Specification	Screw	Wrench
Ø50~Ø100	FTGA03508	TW15S

Assembling



Available inserts E17, E18 Available arbors and bolt E400~E402

